

Zinc Dust Petrolatum

Formerly MIL-T-22361
Superseded by Commercial Spec A-A-59313

This zinc based anti-seize thread compound is generally used to prevent seizing during assembly and disassembly of threaded or unthreaded aluminum and aluminum alloy components. It also provides protection to metal surfaces.

Not for use with optical instruments.

WATER RESISTANT
PROTECTS ALUMINUM AND FERROUS SURFACES
ELECTRICALLY CONDUCTIVE
COMPATIBLE WITH STAINLESS STEEL



DESCRIPTION

This Anti-Seize compound can be used as a lubricant, a sealer, and a tapping compound on plastic as well as metals. The surface need not be cleaned before application unless grit or low quality oil/grease is present. This product reduces assembly friction and increases torque tension by approx. 20%. Use on threaded parts, bushings, gears, valve stems, chain sprockets, levers, hinges, pivots, rollers, heat exchangers, or manifold bolts, or as a gasket release agent.

ADDITIONAL INFO

Available in

8 oz. tube, NSN 8030-00-292-1102
1 lb. can, no NSN

Typical Characteristics:

Color: Silver
Physical State: Paste
Penetration @ 77°F: 206 typical
Specific Gravity: 1.1
Additive Type: Zinc
Flash Point: 360°F

Note: Products listed are suggestions. The information on this site will not replace your testing and evaluation procedures. Ultimate product selection should be based on your test results and the specific performance requirements.

© Armite Laboratories Inc. | All Rights Reserved | 2019
1560 Superior Ave. Suite A4 | Costa Mesa, CA 92627
949-646-9035 | www.armite.com | sales@armite.com