

### **VV-P-236 Technical Petrolatum**

Light Lubricating Grease  
Meets VV-P-236A(2)N3

The petrolatum covered by this specification is intended for use as a light lubricating grease. It may be used as a constituent in certain types of rust preventive compounds.

1. REDUCES FRICTION
2. PREVENTS CORROSION
3. REDUCES TORQUE



### **DESCRIPTION**

VV-P-236 is a light lubricating grease of superior quality. It is not recommended for use as a lubricant in heavily loaded or hot-running bearings.

### **ADDITIONAL INFO**

**Available in:**

1 lb. can, NSN 9150-01-663-8587  
1.75 lb. can, NSN 9150-00-250-0926  
35 lb. pail, NSN 9150-00-250-0928

**Typical Characteristics:**

Color: Reddish  
Physical State: Semi-solid paste  
Penetration (unworked): 150-275  
Specific Gravity: 0.84  
Melting Point: 115-140°F (46.1-60°C)  
Kinematic Viscosity at 212°F (100°C): 11.6-18.0  
Flash Point (open cup): Minimum 390°F (199°C)  
Additive type: None

**Note:** Products listed are suggestions. The information on this site will not replace your testing and evaluation procedures. Ultimate product selection should be based on your test results and the specific performance requirements.

© Armite Laboratories Inc. | All Rights Reserved | 2020  
1218 Commerce Court Suite B | Lafayette, CO 80026  
720-262-5480 | [www.armite.com](http://www.armite.com) | [sales@armite.com](mailto:sales@armite.com)